

**ValueJet**

ValueJet VJ-2638



## Unrivalled Performance for Professional Volume Users

The Mutoh ValueJet 2638 (2600 mm – 102.36") dye sublimation dual head model is ideal for users requiring a versatile floor-to-ceiling production printer. This high speed, high volume sublimation inkjet printer effortlessly delivers sellable production speeds from 46 to 72 m<sup>2</sup>/h and a top speed of 108 m<sup>2</sup>/h.

Ready for printing onto the thinnest sublimation papers, the ValueJet 2638 incorporates the very latest piezo drop-on-demand eight channel head technology and new generation electronics, offering output resolutions ranging from 360 x 360 dpi up to 1440 x 1440 dpi.

### Product Highlights

- Transfer sublimation printing up to 2600 mm (102.36")
- Staggered dual head setup with latest generation 1440 nozzle piezo heads
- Production speeds between 46 & 72 m<sup>2</sup>/h
- Mutoh water-based dye sublimation inks
- Ideal for production of soft signage, linen, home decoration, ...
- Environmentally friendly printing - high level of operator safety

### Application Possibilities

Explore new revenue opportunities such as high quality in-store textile decoration and displays, textile banners, pop-ups, sportswear, personalised home decoration, curtains, linen, gadgets, shirts and many more.



**MUTOH**

Mutoh Belgium - [www.mutoh.eu](http://www.mutoh.eu) / Mutoh Deutschland - [www.mutoh.de](http://www.mutoh.de)  
Mutoh North Europe - [www.mutohnorth.eu](http://www.mutohnorth.eu)



ValueJet VJ-2638



## 102" Dye Sublimation Printer

### Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	2 (staggered setup)
Nozzle Configuration	180 nozzles x 8 lines / head
Drop Mass Range (pl)	3.6 to 35.2
Head Heights (mm)	Low : 1.5 / Middle: 2.5 / High : 4.0

### Media Specifications

Max. Media Width	2600 mm (102.36")
Max. Print Width	2590 mm (101.97")
Max. Media Thickness	0.3 / 1.3 / 2.8 mm *
*: Max. media thickness is specified per head height	
Media Measurements *	Ø 250 mm / 2" & 3" / 100 kg
*: Standard motorised unwinding/winding system	
Media Drying System	Individually controlled pre-heater, fixer & dryer (30 - 50 °C)

### Ink Specifications

Ink Type	Dye Sublimation
Ink Volume	1000 ml
Ink Colours	CMYK
Ink Consumption	8.5 ml / m <sup>2</sup>
UV durability	3 - 6 months outdoor

### Performance

High Quality (720 x 1080)	22.0 m <sup>2</sup> /h
Quality Production (360 x 720)	30.0 m <sup>2</sup> /h
Production (360 x 720)	46.0 m <sup>2</sup> /h
Speed production (360 x 360)	55.0 m <sup>2</sup> /h
Billboard (360 x 360)	72.0 m <sup>2</sup> /h

### Power Consumption

During Printing	< 1000 W
In Stand-by	160 W
Warming Up	≤ 2200 W (main) & ≤ 1850 W (heat)
Power Supply	AC 100-120 V /
	AC 200-240 - 60/50 Hz

### Recommended Working Environment

Temperature	22 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation) with ΔRH: max. 5% RH/h

### Machine Measurements

Width x Depth x Height	3708 x 885 x 1261 mm
Weight Printer	242 kg
Weight Stand	41 kg

Distributed by:

Est. 1991  
**DESIGNSUPPLY**  
 supporting creativity  
 0800 018 23 23  
 sales@designsupply.com

**MUTOH**

© Mutoh Belgium nv. All rights reserved. Rev 1.1 - 07/2014. Specifications subject to change without notice. The machine depicted does not necessarily show a standard configuration. Image in printer provided by Fotolia - www.fotolia.eu. All trademarks mentioned are property of their respective owners.