



HP Designjet T1500 ePrinter series

Newly designed, two-roll, web-connected ePrinter for demanding teams



Innovative user experience

- Eliminate the output clutter—get flat, collated prints thanks to the integrated output stacking tray.
- Gain control—monitor media rolls, view printer status on the touchscreen, and track jobs during printing.
- Load two paper rolls effortlessly—even when seated—with front loading and automatic paper-roll alignment.
- Save space with a compact, 36-inch printer designed with a flat surface for quick checking of your printouts.

Top performance in multi-user environments

- Help cut downtime—print multiple jobs on different media types and sizes with two rolls and smart switching.
- Manage job queues, track print costs, print borderless¹ images, get what you see with true print previews.
- Get dark blacks, true neutral grays, and vivid colors with six Original HP inks and the HP printhead.
- Print complex files fast—one A1/D-size in 21 seconds with a 320-GB hard drive and parallel processing power.

Print from virtually anywhere²

- Use your Apple® or Android™ smartphone or tablet to print from virtually anywhere².
- Access and print projects when you're out of the office, using HP Designjet ePrint & Share² or USB printing.
- Automatically save copies of your projects to the cloud when you print using HP Designjet ePrint & Share².
- Print without drivers using a USB stick or directly email projects to your HP Designjet T1500 ePrinter².

For more information, please visit
hp.com/go/DesignjetT1500

¹ Photo paper is required to print borderless images.

² Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple® iOS or Android™ device and Internet connection are required. Data or connection charges may apply. Print times may vary. 2 GB of temporary storage per account. For more information, visit hp.com/go/eprintandshare



1. With Aurasma installed, please go to the HP Designjet channel at <http://auras.ma/s/ke25m>
2. Without Aurasma installed, please download it:
 - a. Google Play - <http://auras.ma/s/android>
 - b. Apple Store - <http://auras.ma/s/ios>Once done, go to the HP Designjet channel at <http://auras.ma/s/ke25m>
3. Open the application and point to the image to view the HP Designjet video

Technical specifications

Print	Linedrawings	21 sec/page on A1/D, 120 A1/D prints per hour
	Print resolution	Up to 2400 x 1200 optimized dpi from 1200 x 1200 input dpi and Optimization for Photo Paper selected
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) (borderless on photopapers) Sheet: 5 x 22 x 5 x 5 mm (0.2 x 0.87 x 0.2 x 0.2 in)
	Technology	HP Thermal Inkjet
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
	Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)
	Printheads	1 (C, G, M, mK, pK, Y)
	Line accuracy	+/- 0.1% ²
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
	Guaranteed minimum line width	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ³
Media	Handling	Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), basket, automatic cutter
	Weight	60 to 328 g/m ²
	Size	210 to 914-mm (8.3 to 36-in) widesheets; 279 to 914-mm (11 to 36-in) rolls
	Thickness	Up to 0.3 mm (11.8 mil)
Memory	Basic ePrinter: 64 GB (virtual)*, 320 GB hard disk PostScript ePrinter: 64 GB (virtual)*, 320 GB hard disk	
Connectivity ⁵	Interfaces (standard)	Gigabit Ethernet (1000 Base-T), Hi-Speed USB 2.0 certified host connector
	Print languages (standard)	Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFP PostScript ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFP
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows*; HP PCL 3 GUI driver for MacOS X; PostScript Windows, Linux, and Mac drivers ⁶
Dimensions (w x d x h)	Printer	1399 x 693 x 950 mm (55.1 x 27.3 x 37.4 in)
	Shipping	1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in)
Weight	Printer	88 kg (194 lb)
	Shipping	116.5 kg (256.3 lb)
What's in the box	HP DesignJetT1500 ePrinter, printhead, ink cartridges, stacking tray, printer stand, spindles, quick reference guide, setup poster, startup software, power cord	
Environmental ranges	Operating temperature	5 to 40 °C (41 to 104 °F)
	Storage temperature	-25 to 55 °C (-13 to 131 °F)
	Operating humidity	20 to 80% RH
Acoustic	Sound pressure	47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)
	Sound power	6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)
Power consumption		<120 watts (printing), <260 watts (maximum), <4 watts (<7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hard switch)
	Input voltage (auto ranging)	100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current)
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NCE), Korea (KATS)
	Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Certified as Class A product: Korea (KCC)
	Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP
Warranty	One-year limited hardware warranty	

Ordering information

Product	CR356A	HP DesignJetT1500 36-in ePrinter
	CR357A	HP DesignJetT1500 36-in PostScript ePrinter
	CN538A	HP DesignJetT3-in Core Adapter
	COE65A	HP DesignJetT9x0/Tx500 36-in Spindle
Accessories	CQ654B	HP DesignJet HD Scanner
	B3P06A	HP 727 DesignJet Printhead
Original HP printhead	B3P17A	HP 727 40-ml PhotoBlack DesignJet Ink Cartridge
	B3P13A	HP 727 40-ml Cyan DesignJet Ink Cartridge
	B3P14A	HP 727 40-ml Magenta DesignJet Ink Cartridge
	B3P15A	HP 727 40-ml Yellow DesignJet Ink Cartridge
	B3P18A	HP 727 40-ml Gray DesignJet Ink Cartridge
	C1Q11A	HP 727 69-ml MatteBlack DesignJet Ink Cartridge
	B3P23A	HP 727 130-ml PhotoBlack DesignJet Ink Cartridge
	B3P19A	HP 727 130-ml Cyan DesignJet Ink Cartridge
	B3P20A	HP 727 130-ml Magenta DesignJet Ink Cartridge
	B3P21A	HP 727 130-ml Yellow DesignJet Ink Cartridge
	B3P24A	HP 727 130-ml Gray DesignJet Ink Cartridge
	B3P22A	HP 727 130-ml MatteBlack DesignJet Ink Cartridge
	C1Q12A	HP 727 300-ml MatteBlack DesignJet Ink Cartridge
Original HP large format printing materials	C1861A	HP Bright White Inkjet Paper (FSC® certified) ⁸ 914 mm x 45.7 m (36 in x 150 ft)
	C6020B	HP Coated Paper (PEFC™ certified) ⁸ 914 mm x 45.7 m (36 in x 150 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ⁸ 914 mm x 30.5 m (36 in x 100 ft)
	Q8808A	HP Premium Satin Photo Paper (FSC® certified) ⁸ 914 mm x 22.9 m (36 in x 75 ft)
Service and support	U7Z08E	HP 3 year Next Business Day Onsite Support
	U7Z11E	HP 3 year Next Business Day Onsite Support with Defective Media Retention
	U7Z88E	HP 3 year 4-hour response, 9x5 Onsite Support
	U7Z91E	HP 3 year 4-hour response, 13x5 Onsite Support
	U7Z94PE	HP 1 year Post Warranty, Next Business Day Onsite Support
	U7Z99PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enables less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy⁰ as well as dark blacks and true neutral grays¹⁰. For more information, visit hp.com/go/OriginalHPInks

For the entire HP Large Format Printing Materials portfolio, please see hp.com/go/lfp/printing/materials-supplies

- Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original HP inks.
- +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever is greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and HP Original HP inks.
- Measured on HP Matte Film.
- Based on 1.5 GB RAM.
- Includes an embedded JetDirect print server.
- Included with PostScript printers only.
- Available by the end of 2013.
- FSC® trademark license code FSC®-C017543, see fsc.org. PEFC™ trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.
- Can be recycled through commonly available recycling programs.
- Applicable to HP DesignJet-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.



For more information, please visit
hp.com/go/DesignJetT1500

Est. 1991

DESIGN SUPPLY
supporting creativity

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. PANTONE is the property of Pantone, Inc. Apple is a trademark of Apple Computer, Inc., registered in the U.S. and other countries.

4AA4-5694EEW, June 2013

