

Large Format Print Solutions ideal for CAD & GIS

The imagePROGRAF iPF770 is a 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.



Key features:

- High-volume continuous printing, with 130 ml hot-swap ink tanks that can be replaced while the unit is printing
- A0 output in Fast Economy mode in 48 seconds
- Space saving – Unique compact design to fit anywhere
- Highly accurate with 0.02 mm minimum line width and +/-0.1 % line accuracy
- 5-colour dye-and-pigment ink system with new magenta ink for reproduction of brighter red colour
- Printing PDF / TIFF / JPEG / HP-GL2 easily, from general graphics to CAD and GIS drawings, with bundled Direct Print & Share Utility
- Cloud ready for immediate sharing, with easy access even from mobile devices
- Use the bundled PosterArtist Lite software and Print Plug-in for Microsoft Office to create powerful large format posters with ease
- Manage costs and track ROI with full accounting tools

iPF770

36
INCH

2,400 X
1,200 DPI

130 ML
INK TANKS

ECONOMY
PRINTING MODE

5 COLOUR WITH
NEW MAGENTA

A0 48 SECONDS

15,360
NOZZLES

BORDERLESS
PRINTING

Specifications

iPF770

TECHNOLOGY

Printer Type	5 Colour - 36" / 914.4 mm
Print Technology	Canon inkjet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
Print Resolution	2,400 x 1,200 dpi
Nozzle Pitch	1,200 dpi x 2
Guaranteed Minimum Line Width	0.02 mm
Line Accuracy	±0.1 % or less
Ink Droplet Size	4 Picoliter per colour
Ink Capacity	Bundled Starter Ink: 90 ml Sales Ink: 130 ml
Ink Type	Dye / Pigment Reactive Ink Dye: Cyan, Magenta, Yellow, Black Pigment: Matte Black
OS Compatibility	32 bit - Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 64 bit - Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 / 2008R2, Windows Server 2012 / 2012R2 Mac: OSX - 10.6.8 - 10.10.x
Printer Languages	GARO (Graphic Arts Language with Raster Operations), HP-GL/2, HP RTL
Standard Interfaces	USB 2.0 High-Speed Ethernet 10 / 100 / 1000 Base-T/TX

PRINTING SPEED

A0 Size, Plain Paper	0:48 min (Fast Economy Mode) 0:48 min (Fast Mode) 1:15 min (Standard Mode)
A0 Size, Coated Paper	1:15 min (Fast Mode) 2:24 min (Standard Mode) 3:50 min (High Quality Mode)

MEMORY

Buffer RAM	256 MB
-------------------	--------

PAPER HANDLING

Media Width	Roll Paper: 10" / 254 mm - 36" / 914.4 mm Cut Sheet: 8" / 203.2 mm - 36" / 914.4 mm
Media Thickness	Roll Unit: 0.07 - 0.8 mm Top Loading Manual Feed: 0.07 - 0.8 mm
Minimum Printable Length	Roll: 203.2 mm Cut Sheet: 279.4 mm
Maximum Printable Length	18 m (Varies according to the OS and application)
Maximum Media Roll Diameter	150.0 mm

Paper Feed Method

Borderless Printing Width (Roll Only)

DIMENSIONS AND WEIGHT

Physical Dimensions (W x D x H)

Weight

Software Included

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Noise Level (Approx.)

Regulations

Environment Certificates

WHAT'S INCLUDED

What's In The Box?

OPTIONS

Roll Holder Set

CONSUMABLES

Ink Tanks

Print Head

Maintenance Cartridge

Roll Feed: One Roll, Top Loading, Front Output
Top Loading Manual Feed: One Sheet, Front Output
10" (254 mm), B4 (257 mm), A3 (297 mm), Banner (300 mm),
14" (356 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm),
A1 (594 mm), 24" (610 mm), B1 (728 mm), A0 (841 mm), 36" (914 mm)

1,304 (W) x 887 (D) x 1,062 (H) mm (With basket open)
1,304 (W) x 1,100 (D) x 1,062 (H) mm (When basket is at the extended position for flatbed stacking)

64.6 kg (roll holder included, no inks, no print heads)

Canon Printer Driver, Status Monitor / Print Monitor, Printer Driver
ExtraKit - Free Layout and IR enlargement Copy, Printer Driver
Optimization Module for AutoCAD, Media Configuration Tool,
PosterArtist Lite (PC only), Print Plug-in for Microsoft® Office (PC
only), Direct Print & Share, Custom Installer Creation Tool

AC 100 - 240 V (50 - 60 Hz)

Operation: 140 W or less

Power Off Standby: 0.5 W or less

15 - 30°C, 10 - 80 % (Condensation free)

Operation: approx. 48 dB

Standby: 35 dB or less

Acoustic Power: 6.5 Bels

Based on ISO 7779

Europe: CE mark,

Germany: TUV mark,

Russia: EAC

Other Countries: CB Certification

ENERGY STAR, RoHS (EU), WEEE (EU), ErP Directive (Lot6, 26),
China RoHS, Chemical Substances Regulation, Battery certification
(EU, Japan, USA, China, Taiwan), Packing material Regulation (EU,
USA, Korea)

1 print head, 1 set of starter ink tanks (C, M, Y, BK, 2 x MBK - 90 ml),
3 inch core adapters, set up guide, User software CD-ROM (Mac
& Win), Carrying caution leaflet, Safety / Standard Environment
leaflet, PosterArtist Lite leaflet, PosterArtist Lite software CD-ROM,
Announcement of LFP Survey Program, EAC leaflet, Quick guide

RH2-33

PFI-107: 130 ml - C, M, Y, BK, 2 x MBK

PF-04

MC-10

Est. 1991

DESIGNSUPPLY

supporting creativity

0800 018 23 23

sales@designsupply.com

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2014

Canon (UK) Ltd
Woodhatch
Reigate
Surrey RH2 8BF
Telephone no 01737 220000
Facsimile 01737 220022
canon.co.uk

Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co.Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie



imagePROGRAF



Canon