

- Reliable production of large format advertisements, graphics and posters.

The imagePROGRAF PRO-6000S is the best solution for very large format (up to 60") printing productivity, delivering outstanding production quality at high speed, and offering exceptional reliability.



- Outstanding LUCIA PRO 8-colour print quality at impressive speeds, with up to 60" large format production output.
- A new 1.28" wide print head enables faster printing while maintaining high quality.
- Dual roll unit supports continuous paper feeding or automatic take-up of printed output.
- Visually attractive and distinctive, black body hardware design.
- Ergonomic design with a flat top surface for print checking and a 3.5" colour LCD touch screen operation panel.

- Introducing the optimum space-saving compact body for production environments.
- Fast and easy printing of PDF and JPEG file formats directly from USB memory stick.
- Wi-Fi functionality for easy connection and quick setup to wireless networks.
- High-capacity "hot swap" ink tanks for uninterrupted printing.
- Guaranteed colour consistency between jobs and different production sites.

TECHNOLOGY**Printer Type****Print Technology****Number of Nozzles****Print Resolution****Nozzle Pitch****Line Accuracy****Ink Droplet Size****Ink Capacity****Ink Type****OS Compatability****Printer Languages****Standard Interfaces****MEMORY****Standard memory****Hard Drive****PRINT TIME FOR A0 PAGE SIZE****Plain Paper****Coated Paper****Glossy Photo Paper****MEDIA HANDLING****Media Feed and Output****Media Width****Media Thickness****Minimum Printable Length****Maximum Printable Length****Maximum Media Roll Diameter****Media Core Size****Margins Recommended area**

8 Colour 60"/1524 mm
Canon Bubblejet on Demand 8 colours integrated type (12 chips per print head x 1 print head)
18,432 nozzles (1536 nozzles x 12 colour)*
*The four key colours (C, M, Y, MBk) are arranged symmetrically on the print head
2400 dpi x 1200 dpi
600 dpi x 2 includes Non-firing nozzle detection and compensation system
±0.1% or less
User adjustments necessary. Printing environment and media must match those used for the adjustments.
CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
minimum 4 pl per colour

Sales ink: 160ml/330ml/700ml
Bundled Starter ink: 330ml (C, M, Y, MBk), 190ml (PC, PM, BK, GY)

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey
Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2
Apple Macintosh: OS X 10.7.5 - 10.11
SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

USB A Port: USB Memory Direct Print for JPEG/PDF files
USB B Port: Built-in Hi-Speed USB 2.0
Ethernet: 10/100/1000 base-T
Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

3 GB
320 GB

Print Mode	Print Time
Fast	0:55 min
Standard	2:51 min

Print Mode	Print Time
Fast	1:35 min
Standard	2:51 min

Print Mode	Print Time
Fast	2:58 min
Standard	4:46 min

Roll Paper: Two Roll, Front-loading, Front Output
Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 mm - 1524 mm

Cut sheet: 203.2 mm - 1524 mm

Roll/Cut: 0.07 mm - 0.8 mm

203.2mm

Roll paper: 18 m (Varies according to the OS and application)

Cut sheet: 1.6 m

170 mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm

Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area**Media Feed Capacity****Media Take-up roll unit****Borderless Printing Width (Roll Only)****Maximum number of delivered prints****DIMENSIONS AND WEIGHT****Physical Dimensions WxDxH (mm) and Weight (Kg)****Packaged Dimensions WxDxH (mm) and Weight (Kg)****POWER AND OPERATING REQUIREMENTS****Power Supply****Power Consumption****Operating Environment****Acoustic Noise (Power/Pressure)****Regulations****Environment Certificates****WHAT'S INCLUDED****What's in the Box?****Software Included****OPTIONS****Optional Items****CONSUMABLES****User Replaceable Items**

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm
Roll Paper: Two roll automatic switching possible
Cut Sheet: 1 sheet
Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll
515 mm(JIS B2), 728 mm(JIS B1), 1030 mm(JIS B0), 594 mm(ISO A1), 841 mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60", 257 mm(JIS B4)*, 297 mm(ISO A3)*, 329 mm(ISO A3+)*, 420 mm(ISO A2)*, 8", 16", 30", 300 mm*

*Some environmental conditions may not produce the desired result.

Standard position: 1 sheet
Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1999 mm x 984 mm x 1168 mm (Basket Opened)
1999 mm x 766 mm x 1168 mm (Basket Closed)
Weight approx x 137 kg (excluding ink and print heads)
Printer: (Main unit and stand with pallet):
2227 mm x 915 mm x 1022 mm,
Weight approx: 211 kg
Roll unit: 2133 mmx 562 mmx 461 mm,
Weight approx: 40 kg

AC 100-240V (50-60Hz)
Operation: 113 W or less
Standby: 1.8 W or less
Power off: 0.5 W or less
Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Operation: 49 dB (A)
(Glossy paper, Print priority: Standard)
Standby: 35 dB (A) or less
Operation: 6.7 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)
Europe: CE mark, Germany: TUV mark, Russia: EAC, Other countries: CB certification
International Energy Star Program (WW), RoHS

Printer, 1 x print head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard Environment Leaflet, User Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet
imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

Roll Unit: RU-61 *This is a mandatory item
2/3" Roll Holder: RH2-65

Ink Tank: PFI-1100 (160 ml), PFI-1300 (330 ml), PFI-1700 (700 ml)
Print Head: PF-10
Cutter Blade: CT-07
Maintenance Cartridge: MC-30



Crystal-fidelity

Est. 1991
DESIGN SUPPLY
supporting creativity

0800 018 23 23

sales@designsupply.com

Canon

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc.

canon.com

Canon Europe

canon-europe.com

English edition

© Canon Europa N.V., 2016