

imagePROGRAF TX-3000

PIONEERING HIGH- PERFORMANCE LARGE-FORMAT MODEL WITH STUNNING VERSATILITY.



Est. 1991
DESIGNSUPPLY 
supporting creativity

The advanced 36-inch large-format inkjet ideal for CAD, GIS and Poster printing. Engineered to deliver superb precision, efficient output, reassuring security credentials and low-cost operation.



- Productive output speeds from the new print head design, and continuous printing option
- Supreme accuracy and peerless precision thanks to LUCIA TD ink
- Simple user operation, with dual-roll feeding available for the first time on a 36-inch model
- Brilliant colour gamut on plain media and superb performance on uncoated paper
- Straightforward control thanks to easy roll loading, touchscreen display and direct printing from USB
- Print to any network-connected TX-Series unit via the universal driver
- Neat and slender, the TX-3000 fits easily into compact office spaces
- Class-leading reliability, with unparalleled uptime and rock-solid security
- Take full advantage of weather-resistant media, perfect for CAD, GIS and outdoor Posters
- Bundled software helps to ensure smooth large-format-printing workflows

PRODUCT RANGE



Canon

Explore. Inspire. Improve.

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3000

TECHNOLOGY			
Printer Type	5 Colour - 36"/914.4mm	Borderless Printing Width (Roll Only)	[Recommended] 515mm(JIS B2), 594mm(ISO A1) 728mm (JIS B1), 841mm (ISO A0), 10", 14", 17", 24", 36"
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)		[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 8", 12", 16", 20", 30", 300mm, 500mm, 600mm, 800mm
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each		
Print Resolution	2,400 x 1,200 dpi	DIMENSIONS AND WEIGHT	Printer unit with basket open and printer stand: 1389 x 984 x 1168 mm (Basket Open) Weight: 105 kg (including Roll Holder)
Nozzle Pitch	1,200 x 2 includes Non-firing nozzle detection and compensation system	Physical Dimensions - (W x D x H)	imagePROGRAF TX-Series Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.
Guaranteed Minimum Line Width	0.02 mm	Software Included	
Line Accuracy	±0.1 % or less	POWER AND OPERATING REQUIREMENTS	
Ink Droplet Size	5 Picoliter per colour	Power Supply	Input Power: AC 100-240 V (50-60 Hz)
Ink Capacity	Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y) Sales Ink: 160ml/330ml/700ml	Power Consumption	Power consumption (using wired LAN): 105 W or less
Ink Type	Pigment ink: 5 colour MBK/BK/C/M/Y		At sleep mode (using wired LAN): 3.6 W or less At sleep mode (using all ports): 3.6 W or less
OS Compatability	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/ R2, Server 2012/R2		<EU only - data for ErP Lot 26>
Printer Languages	Apple Macintosh: OS X 10.7.5 - 10.11 HP-GL/2, HP RTL, PDF, JPEG - for details check specifications		At the power off: 0.3 W or less
Standard Interfaces	USB B Port: Type: Built in (Hi-Speed USB) Mode: Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer		Default setting for the time to enter the Sleep mode: 30sec
	Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T IEEE 802.3u 100base-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation IEEE 802.3x Full Duplex		<EU only - data for ErP Lot 26>
	Protocol: SNMP (Canon-MIB, HTTP, TCP/IP (IPv4/IPv6), ftp		15 - 30°C, 10 - 80 % (Condensation free)
	Wireless LAN: Standard: IEEE802.11n/IEEE802.11g/IEEE802.11b		Operation : 51dB(A) or less (Plain paper, line drawing, standard mode)
	Security: WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)		Stand by : 35dB(A) or less (Measured on ISO7779 standard)
MEMORY			Europe: CE mark Russia: EAC, Other Countries: CB certification
Standard memory	128GB (Physical memory 2GB)		ENERGY STAR (WW), RoHS directive, IT ECO Declaration (Europe), WEEE
Expansion slot	No		
HARD DISK	500GB (Encrypted)	WHAT'S INCLUDED	
		What's in the Box?	Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet
PAPER HANDLING		OPTIONS	
Media Width	Roll paper: 8"/203.2mm - 36"/914.4mm Cut sheet: 8"/203.2mm - 36"/914.4mm	Optional Items	Roll Unit: RU-32 Stacker: SS-31 2/3" Roll Holder: RH2-34
Media Thickness	0.07 - 0.8mm		
Minimum Printable Length	203.2mm		
Maximum Printable Length	Roll Paper: 18m (varies according to the OS and application) Cut Sheet: 1.6m		
Maximum Media Roll Diameter	170 mm	CONSUMABLES	
Paper Feed Method	Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)	User Replaceable Items	Print Head: PF-06 Ink Tanks: PFI-110 Cutter Blade: CT-07 Maintenance Cartridge: MC-30



LUCIA TD
ink

Est. 1991

DESIGNSUPPLY

0800 018 23 23

sales@designsupply.com

Canon

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition

© Canon Europa N.V., 2017

Explore. Inspire. Improve.