

LARGE-FORMAT MFP OFFERING EXCEPTIONAL QUALITY, IMPRESSIVE SPEED AND INTUITIVE OPERATION.



- Neatly integrated chassis of the TX-3000 MFP T36 allows it to fit into crowded environments
- Accelerate productivity with advanced print head and continuous printing capability
- Simultaneous printing and scanning serves up even greater workflow efficiency
- Minimise upkeep requirements with dual-roll feeding, unique to a 36-inch MFP, and simplified roll replacement
- Economical operation made possible by LUCIA TD ink, delivering sharp detail even on cheaper uncoated paper
- Consistently accurate scanning ensured by Colortrac SingleSensor technology
- Convenient 15.6-inch colour touchscreen display and new SmartWorks user interface offers easy operation
- Flexibility to print to any network-connected TX-Series unit, thanks to universal printer driver
- Reassuring reliability provided by class-leading security specs
- Weather-resistant media printing, and board-media scanning of up to 2-mm thick

Outstanding efficiency in tandem with unparalleled performance, from a 36-inch large-format multifunction inkjet printer built for the most exacting CAD, GIS and Poster production assignments.



PRODUCT RANGE



Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3000 MFP T36

SCANNER TECHNOLOGY

Scan Technology	SingleSensor
Optical Resolution (dpi)	1200
Paper path	Flat
Scan width	36" (914mm)
Min scan width	6" (15cm)
Document width	38" (965mm)
Max scan length	8m (JPEG/PDF), 15.2m (TIFF)
Weight of scanner	15Kg
Dimensions W x D x L	1109 x 324 x 153 mm
Power Supply	External power supply 100-240VAC autosensing +/-10%, 50-60Hz
Compliances	Energy Star National/CB Russia/EAC EU/CE
Front/rear exit	Rear (front eject via Document Return Guide)
Document handling - Face up/down	Up
Document thickness	2.0mm(1)
Scan speed (inches/sec) 8-bit grayscale & mono @200dpi (2)	13
Scan speed (inches/sec) 24-bit color @200dpi (2)	6.0
Interface USB	3.0 (backward compatible to USB2)
Scanner controls	Stop, Advance/Rewind, LED status
Branding/Colour	None / Canon black
Software (included)	SmartWorks MFP V5
OS for software	Win 8/10 (32/64 bit)
What's in the box	<ul style="list-style-type: none"> T36 scanner Stand assembly 2 paper edge guides Document return guides (3 for T36) Calibration target CD for SmartWorks MFP software and PDF documentation: T25 /T26 Scanner User Manual and Quick Start Guide. T36 Scanner Quick Start Guide. USB3 cable (3 meter) Power Supply Regional - Mains power cord(s) (2 meter)

EITHER LCD OPTION CAN BE SELECTED*

*Not available in all countries

LCD Flat Panel - PC Included

LCD Type: All in One: 15.6" TFT Display, Multi-touch PC (included): System: Windows 10 Enterprise LTSB, CPU: Intel Celeron G3900 2.3GHz, RAM: 4GB DDR4, HDD: SATA 500GB, 3 x USB3 & 1 USB2 & 1 x GbE (rear), 1 x USB3 (Front)

LCD Type: 15.6" Flat Panel Touch-Screen Display

LCD Flat Panel - PC Excluded

PRINTER TECHNOLOGY

Printer Type	5 Colour - 36"/914.4mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
Print Resolution	2,400 x 1,200 dpi
Nozzle Pitch	1,200 x 2 includes Non-firing nozzle detection and compensation system
Ink Capacity	Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y) Sales Ink: 160ml/330ml/700ml
Ink Type	Pigment ink 5 colour MBK/BK/C/M/Y
OS Compatability	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11
Printer Languages	HP-GL/2, HP RTL, PDF, JPEG - for details check specifications
Standard Interfaces	USB B Port: Type: Built in (Hi-Speed USB) Mode: Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T IEEE 802.3u 100base-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation IEEE 802.3x Full Duplex

Protocol:
SNMP (Canon-MIB), HTTP, TCP/IP (IPv4/IPv6), ftp

Wireless LAN:
Standard:
IEEE802.11n/IEEE802.11g/IEEE802.11b

Security:
WEP (64/128bit)
WPA-PSK (TKIP/AES)
WPA2-PSK (TKIP/AES)

128GB (Physical memory 2GB)

No

500GB (Encrypted)

Roll paper: 8"/203.2mm - 36"/914.4mm

Cut sheet: 8"/203.2mm - 36"/914.4mm

0.07 - 0.8mm

203.2mm

Roll Paper: 18m (varies according to the OS and application)

Cut Sheet: 1.6m
170 mm
Roll Paper: Front loading, front output
Cut Sheet: Front loading, front output
(Manual feed using media locking lever)
[Recommended] 515mm(JIS B2), 594mm(ISO A1), 728mm (JIS B1), 841mm (ISO A0), 10", 14", 17", 24", 36",
[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 8", 12", 16", 20", 300mm, 500mm, 600mm, 800mm

MEMORY

Standard memory
Expansion slot

HARD DISK

PAPER HANDLING

Media Width

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Paper Feed Method

Borderless Printing Width (Roll Only)

DIMENSIONS AND WEIGHT

Software Included

WHAT'S INCLUDED

What's in the Box?

imagePROGRAF TX-Series Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet

Roll Unit: RU-32
Stacker: SS-31
2/3" Roll Holder: RH2-34

OPTIONS

Optional Items

Print Head (PF-06)
Ink Tanks (PFI-10)
Cutter Blade (CT-07)
Maintenance Cartridge (MC-30)

NOTES & RECOMMENDATIONS

1. Thick documents up to 2mm must be flexible and the paper return guide removed. Some media should be scanned at reduced speeds to obtain optimal image quality. Colortrac cannot guarantee to scan all media. For large media Colortrac recommend the scanner be placed on a flat surface and the operator supports the document as it enters and exits the scanner.
2. The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. True 200 x 200dpi image capture. Competitors quote scan speeds using 'Turbo', 'Normal' or 'High Speed' modes that reduce image quality whilst suggesting that scan resolution is doubled. These modes use software interpolation to create 'virtual image pixels' from a lower resolution scan thereby increasing the number of pixels in the scan direction (&/or X-direction) in an attempt to simulate higher image resolution. Colortrac SmartLF scanners are designed to scan images fast at the optimum resolution required to capture the original image detail without compromising quality.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Est. 1991

DESIGNSUPPLY

0800 018 23 23
sales@designsupply.com

Canon Inc.

canon.com

Canon Europe

canon-europe.com

English edition

© Canon Europa N.V., 2017

Explore. Inspire. Improve.