

# UNLEASH HIGH QUALITY PRINTS WITH THIS INNOVATIVE 36-INCH LARGE-FORMAT INKJET PRINTER



TM-305



TM-300

A 60% noise reduction and compact design, the imagePROGRAF TM-300 and TM-305 can fit into small office space. Even on plain paper, the full pigment Lucia TD ink prints precise lines, crisp text and vivid colour with enhanced water resistance.



TM-305

## PRODUCT RANGE



TM-300 MFP T36



TM-305 MFP T36



TM-205

# TECHNICAL SPECIFICATIONS

imagePROGRAF  
TM-300\TM-305

	TM-300	TM-305	TM-300	TM-305
<b>TECHNOLOGY</b>				
Printer Type				
Print Technology				
Print Resolution	5 Colour 36"/914mm	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	Media Feed Capacity	Manually switchable by user
Number of Nozzles	15,360 nozzles (MBK 5,120 nozzles, Other Colours 2,560 nozzles each)	2,400 x 1,200 dpi	Borderless Printing Width (Roll Only)	515mm (JIS B2), 728mm (BIS B1), 594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36" [Printable] 257mm (JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 8", 12", 16", 20", 30", 300mm, 500mm, 600mm, 800mm
Line Accuracy	±0.1% or less	1,200 dpi (2 lines)	Maximum number of delivered prints	Stand/Basket - Standard position: 1 sheet Stand/Basket - Flat position: 20 sheets on A1, A2 landscape <sup>(1)</sup>
Nozzle Pitch	minimum 5 pl per colour			
Ink Droplet Size	Sales Ink: 130ml /300ml			
Ink Capacity	Bundled Starter Ink: 130ml (Matte Black)/90ml (Black, Cyan, Magenta, Yellow)			
Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow			
OS Compatability	Microsoft Windows 32 Bit: Windows 7, 8.1, 10, 64 Bit: Windows 7, 8.1, 10, Server 2008R2, Server 2012/2012R2, Server 2016	Physical Dimensions WxDxH (mm) and Weight (Kg)	Main Unit, Stand and Basket 1289 x 887 x 1060 mm (Basket Open) 1289 x 757 x 1060 mm (Basket Closed)	
Printer Languages	Apple Macintosh: OS X 10.10.5 - OS X 10.11, macOS 10.13	Packaged Dimensions WxDxH (mm) and Weight (Kg)	60 kg (including Roll Holder Set, excluding ink and print head)	
Standard Interfaces	SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02)	Power Supply	Printer (Main unit with stand (SD-32) and pallet): 1462 x 913 x 961 mm, 105 kg	
	USB A Port: USB Memory Direct Print	Power Consumption		
	USB B Port: Built-in Hi-Speed USB	Operating Environment		
	Ethernet: IEEE 802.3 10-base-T/IEEE 802.3u 100base-TX/IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex	Acoustic Noise (Power/Pressure)	AC 100-240V (50-60Hz)	
	Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b	Regulations	Operation: 69 W or less Sleep mode: 3.6 W or less	
		Certificates	Default setting for the time to enter the Sleep mode: Approx. 5 Minutes	
			Power off: 0.3 W or less	
			Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)	
			Operation: 44 dB (A) (Plain paper, line drawing, standard mode)	
			Standby: 35 dB (A) or less	
			Operation: 6.0 Bels (Plain paper, line drawing, standard mode) (Measured on ISO 7779 standard)	
			Europe: CE mark, Russia: EAC TUV, CB	
<b>MEMORY</b>				
Standard memory	2 GB	128GB with 2GB Physical Memory		
Hard Drive	N/A	500GB		
<b>PRINTING SPEED</b>				
CAD Drawing:				
Plain Paper (A0 Roll)	0:40 (Fast Economy Mode) 0:46 (Fast) 1:14 (Standard)			
Poster:				
Plain Paper (A0 Roll)	0:44 (Fast) 1:18 (Standard)	What's included		
Heavy Coated Paper (A0 Roll)	1:41 (Fast) 2:36 (Standard)	What's in the Box?		
<b>MEDIA HANDLING</b>				
Media Feed and Output				
Media Width	Roll paper: One Roll, Upper-loading, Front Output Cut sheet: Upper-loading, Front Output (Manual feed using media locking lever)	Software Included		
Media Thickness	Roll paper: 203.2 - 917 mm Cut sheet: 203.2 - 917 mm			
Minimum Printable Length	Roll/Cut: 0.07 - 0.8 mm			
Maximum Printable Length	Roll paper: 203.2 mm Cut sheet: 279.4 mm			
Maximum Media Roll Diameter	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m			
Media Core Size	150 mm			
Margins Recommended area	Internal diameter of roll core: 2"/3"			
Margins Printable area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm			
	Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet for Apple AirPrint Only: Top: 3 mm, Bottom: 12.7 mm, Side: 3 mm			
	Cut sheet for others: Top: 3 mm, Bottom: 20 mm, Side: 3 mm			



Canon



E | sales@designsupply.com  
T | 020 7942 1555 | W | www.designsupply.com  
Unit 2, Green Lane Business Centre, New Eltham, London, SE9 3TL

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.<sup>™</sup> and <sup>®</sup>: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

## Footnotes

<sup>(1)</sup> Excludes strong curling conditions